

# Bolt feeder

## BOLT FEEDER AUTOMATIC · LOW NOISE

- Feeding capacity: up to 30 bolts per minute.
- Single or dual feeding.
- Top cover for low noise and high protection.
- Control cabinet allow future upgrades.
- CE safety Norms.



### TECHNICAL FEATURES

### SINGLE FEED

### DUAL FEED

Power supply / Frequency	400 V <sub>ac</sub> / 50-60 Hz	
Operating power	24 V <sub>dc</sub>	
Consumption	300 VA	350 VA
Feeding capacity (bolts per minute)	26 to 29	24 to 30
Cycle time	2 s	4 s
Hopper capacity	10 litres	
Nominal air pressure	6 bar	
Feeding head stroke / mounting angle	156 mm / 30°	
Bolt impeller / selector	10 bar	
Bolt transport (to feeding head / centering device)	Pneumatic / Mechanic	
Noise level	72 db	
External dimensions (H x W x L)	1400 x 507 x 560 mm	
Weight (Without feeding head / feeding head)	144,5 / 8,5 kg	149,5 / 8,5 (x2) kg
Feeding head interconnection length	3000 mm	3000 (x2) mm
Feeding head length	750 mm	750 (x2) mm



Dedicated feeders under request

**SERRA**