

PRIMA Welders




Punto 8	
Rated Power @ 50%	8 KVA
Max Power	65 KVA
Fuses at 400 v 50Hz	32 Amp
Secondary No Load Voltage	5 V
Max secondary welding current	13,000 Amps
Secondary Short Circuit Current	11,500 Amps
Duty Cycles	8%
Welding Capacity On Mild Steel	2 x 2.5 mm
Electrode Force At 6.5 bar	300 daN
Electrode Force At 8.0 bar	450 daN
Water cooling	Built In
Throat Depth	120mm
Electrode Arm Diameter	20mm
Electrode Arm Length	120mm—500mm
Electrode Stroke	12 + 55mm
Working Height	2500mm
Max Radius	2300mm
Dimensions Rest Position WxLxH	1030x815x1250mm
Welding Gun Dimensions WxLxH	130x350x380mm

The PUNTO range of bodyshop welders are fitted with a mobile balancing arm enabling the operator to raise and manoeuvre the gun without any effort.



An attachment DPC can be fitted to the X gun to convert to C gun.



B13 130mm B1 200mm B2 300mm B3 400mm B4 200mm B5 400mm B10 250mm B11 500mm B12 B500 Water Cooled Arms



E22 E37 E4 E36 E24 E25



Prospot Limited - Unit C Riverside Industrial Estate
 Atherstone Street - Fazeley - Tamworth - Staffordshire - B78 3RW
 Telephone: 01827 254 829 - Fax: 01827 254 832
 Email: sales@prospot.co.uk - Web: www.prospot.co.uk